



# Geberit Kombifix element for wall-hung WC, 82 cm, with Omega concealed cistern 12 cm



## APPLICATION PURPOSES

- For masonry walls
- For installation in part-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For dual flush

## CHARACTERISTICS

- Powder-coated mounting frame
- Mounting frame with four fixing brackets
- Adjustable installation depth, 12–20.5 cm
- Fastening for connection bend can be mounted without tools from front
- Concealed cistern with top or front actuation
- Concealed cistern, fully insulated against condensation
- Immediate post flush possible with factory setting

- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the left or rear left
- Protection box for service opening can be cut to length
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- Fastening option for electrical connection

## TECHNICAL DATA

Flow pressure	0.1–10 bar
Flush volume, factory setting	6 / 3 l
Flush volume large, adjustment range	4 / 4.5 / 6 / 7.5 l
Flush volume small, adjustment range	2–4 l
Flow rate at 3 bar	0.16 l/s
Product material	Steel

## SCOPE OF DELIVERY

- Water supply connection R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Connection set for WC, ø 90 mm
- Connection bend made of PE-HD, ø 90 mm
- Adapter socket made of PE-HD, ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- Fastening material

## ACCESSORIES

- Geberit Kombifix set of leg supports
- Geberit Kombifix set of studs with foot plate

## INFO

- Actuator plate has to be ordered separately

Art. no.	B cm	H cm	T cm	
110.001.00.1	42	82	12	